

	Specifications	Revision:	V1.0
	CW fiber laser	Date:	202403
	Mode: YFCW-200-SM-050HA	Page:	1/3

1. Optical characteristics

No.	Characteristics	Parameter value	Unit
1	Output power	200	W
2	Central wavelength	1080 ± 2	nm
3	Spectral width	< 5	nm
4	Power adjustment range	10 - 100	%
5	Maximum modulation frequency	50	kHz
6	Laser switching ON/OFF time	< 15	μs
7	Output power instability	< 3	%
8	Beam quality M^2	< 1.2	/
9	Polarization direction	Random	/
10	Indicator light	Yes	/
11	QBH divergence angle (full angle)	< 170	mrad
12	Delivery cable length	5	m



	Specifications	Revision:	V1.0
	CW fiber laser	Date:	202403
	Mode: YFCW-200-SM-050HA	Page:	2/3

2. Electrical characteristics

No.	Characteristics	Parameter value	Unit
13	Power supply voltage	48	VDC
14	Working current	<15	A
15	Power consumption	<800	W
16	Recommended power supply	>800	W

3. Environmental characteristics

No.	Characteristics	Parameter value	Unit
17	Operating temperature	0-40	°C
18	Storage temperature	0-60	°C
19	Cooling method	Air cooling	/


4. Structural characteristics

No.	Characteristics	Parameter value	Unit
20	Laser dimension	439*448*135(with handle)	mm
21	Net weight	<30	kg




	Specifications	Revision:	V1.0
	CW fiber laser	Date:	202403
	Mode: YFCW-200-SM-050HA	Page:	3/3

5. Structural characteristics



Laser dimension



QBH dimension



A leading supplier of advanced lasers for precision manufacturing
<https://en.gzlasertech.com/>